

IP-CALK10L31C

QSFP28 100Gbps LR4 10km DDM Transceiver

PRODUCT FEATURES

- Supports Hermetic package
- Supports 103.1Gbps and 112Gbps aggregate bit rate
- Compliant 4x25Gbps to 4X28Gbps electrical interface
- Compliant 4x25Gbps to 4X28Gbps DFB LAN-WDM transmitter and PIN/TIA receiver
- Maximum link length of 10km on Single Mode Fiber (SMF)
- Hot pluggable QSFP28 footprint
- Duplex LC receptacles
- Single 3.3V power supply
- Maximum power dissipation<4W
- RoHS-6 compliant and lead-free
- I²C management interface
- 0°C to +70°C case operating temperature



APPLICATIONS

- 100GBASE-LR4 100G Ethernet
- OTN OTU4 4I1-9D1F

COMPLIANCE

- QSFP28 MSA SFF-8665
- IEEE802.3ba 100GBASE-LR4
- ROHS

PRODUCT DESCRIPTION

IP-CALK10L31CH are designed for use in 100 Gigabit Ethernet links on up to 10km reach over SMF. The laser drivers control 4- Distributed Feedback Laser (DFB) with center wavelength of 1296nm, 1300nm, 1305nm and 1309 nm. The optical signals are multiplexed to a single –mode fiber through an industry standard LC connector. They are compliant with the QSFP28 MSA and IEEE 802.3bm 100GBASE-LR4 and CAUI-4. Digital diagnostic functions are available via an I2C interface, as specified by the QSFP+ MSA. The optical transceiver is compliant per the RoHS Directive 2011/65/EU.

Contact Information

Inphilight Technology (WuHan) Co., Ltd

Inphi (WuHan) Opto tech Co., Ltd

ADD: Building 5, Zone E, Guangguxin Center, No.52, Road liufang, Jiangxia district, Wuhan, Hubei, China

Should you need more details about datasheet, contact us, pls.

Revision History

Version No.	Date	Description
1.0	September 2, 2020	Preliminary datasheet

Prurchase service: prurchase@inphitech.com

Support service: support@inphitech.com

Warranty service: warranty@inphitech.com