

# IP-EAMS15M85C

QSFP+40Gb/s SR4 (100~400)m DDM

## PRODUCT FEATURES

- Reliable VCSEL array technology
- Maximum link length of 300m on OM3 Multimode Fiber(MMF) and 400m ON OM4 MMF
- Hot-pluggable QSFP+ footprint
- Single 1x12 MPO receptacle
- Maximum power dissipation<1W
- Four-channel full-duplex transceiver module
- RoHS-6 compliant and lead-free
- Support Digital Diagnostic Monitor interface
- Un retimed XLPP electrical interface
- Commercial operating case temperature range: 0°C to 70°C



## APPLICATIONS

- 40GBASE-SR4 40G Ethernet
- Breakout to 10GBASE-SR Ethernet
- Proprietary interconnections

## COMPLIANCE

- QSFP+ MSA.
- IEEE802.3ba
- SFF-8436
- RoHS

## PRODUCT DESCRIPTION

IP-EAMS15M85C are designed for use in 40 Gigabit per second links over multimode fiber. They are compliant with the QSFP+ MSA and IEEE 802.3ba 40GBASE-SR4. Module-level digital diagnostic functions are available via an I<sup>2</sup>C interface, as specified by the QSFP+ MSA. The optical transceiver is compliant per the RoHS Directive 2011/65/EU.

## CONTACT INFORMATION

Inphilight Technology (WuHan) Co., Ltd

Inphi (WuHan) Opto tech Co., Ltd

ADD: Building 5, Zone E, Guangguxin Center, No.52, Liufang Road, Jiangxia district, Wuhan, Hubei, China

Should you need more details about datasheet, contact us, pls.

## REVISION HISTORY

Version No.	Date	Description
1.0	June 24, 2019	Preliminary datasheet
1.1	January 14, 2021	Add description information

Purchase service: [prurchase@inphitech.com](mailto:prurchase@inphitech.com)

Support service: [support@inphitech.com](mailto:support@inphitech.com)

Warranty service: [warranty@inphitech.com](mailto:warranty@inphitech.com)